

2305 W. 190th St., Torrance, CA 90504 www.RefrigerationX.com

	Project:		
	Model #:		
	Item #:		
	Available W/H:		Qty:
	Approval:		
	AIA #:	SIS #:	
	CSI Section 11400		

Undercounter Freezer

Undercounters X-line

Model : XUF-36-N



____ FEATURES & BENEFITS ____

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, RefrigerationX brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlesssly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with themal efficiency.

Cabinet construction

X-line model boasts a stainless steel exterior (door) with AL exterior sides (galvanized steel back and bottom). Interior is stainless steel floor and back with AL sides. It guarantees the utmost in cleanliness and long product life.

- High-density polyurethane insulation
 The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Self-contained system
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- 4" dia. swivel casters with locks on the front set
- Freezer holds -10°F ~ 0°F for the best in food preservation

						NATURAL Refrigerant	Intertek
Model	Swing Doors	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$ (inches)
XUF-36-N	2	9.74	2	1/3	2.8	238	363/8 x 30 x 30

Ver.20230309 Printed in U.S.A.

* Depth does not include 3" for cutting board and 1" for rear spacers. † Height does not include 5-5/8" for caster height.

Undercounter Freezer

Model : XUF-36-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	2.8				
Compressor HP	1/3				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	9.74				
Ext. Length Overall (in.)	363/8 (923mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.) [†]	30 (762mm)				
# of Doors	2				
# of Shelves	2				
Shelf Size (L x D) (in.)	15 x 17				
Net Weight (lbs.)	223				
Gross Weight (lbs.)	238				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers.

† Height does not include 5-5/8" for caster height.


• WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

OPTIONAL ACCESSORIES


- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- \bullet 5" caster, $\rlap{k2}''$ diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1⁄2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: WM35800100

PLAN VIEW

(unit : inch)



TOP VIEW



SIDE VIEW

Ver.20230309

NATURAL