## **GLASS DOOR BACK BAR COOLER**

### EBB – Series Model : EBB59G





Operating temperature range is 32°F ~ 42°F





#### **Cabinet Construction**

Heavy duty stainless steel countertop, textured and laminated black vinyl exterior. Galvanized steel interior wall, and high quality stainless steel floor. 1 3/4" thick high density foamed-in-place polyurethane insulation. Built-in caster thread receptacles.

#### **Refrigeration System**

- · Side mounted condensing unit
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- $\cdot\,$  Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Environmentally friendly CFC free R-134A refrigerant
- Air defrost controlled by electrical timer
- · Copper tube and aluminum fin evaporator with anti-corrosive coating
- · Energy efficient condensate drain pan assembly heated by high side copper tube
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

#### Doors

- Black PVC door frames
- · Low emissivity double pane glass system reflects UV rays and improves
- · insulation for maximized energy efficiency
- · One piece snap-in magnetic door gaskets for easy replacement
- Heavy duty die cast door handles
- Door locks

#### Lighting

 Shielded vertical LED interior lighting with on/off switch for energy saving, less heat generation and enhanced illumination (available from 2015 models)

#### Shelving

- · Two epoxy coated wire shelves per section
- · Stainless steel pilasters and shelf clips

#### **Temperature Control**

- Factory preset temperature, 35°F
- Temperature setting range from 32°F to 42°F
- Easy to set analog thermostat

#### Option

· 2 1/2" and 4" diameter casters (3 1/2" and 5" overall height)

Model	# of	<b>Capacity</b> ►	НР	Refrigerant	# of	Capacity 20 oz.	Power	Amps	Crated	Exter	ior Dimensio	ns
mouor	Doors	(Cu. Ft.)		nonigorant	Shelves	Cans / Bottles	(V-Hz-Ph)	Ampo	Weight	L	$\mathbf{D}^+$	Н
EBB59G	2	20.09	1/4+	R-134A	4	640 / 408	115-60-1	4.50	322 lbs (146.1 kg)	57 3/4" (596 mm)	27'' (685 mm)	37 1/4" (946 mm)

† : Depth does not include protruding door handles

Specifications subject to change without notice.

Product dimensions are for general purposes and not absolute value. Product capacity(r) is calculated based on standard industry figures. Slight variations may exist. If dimensions and capacity are critical, please contact Everest Refrigeration.

# **GLASS DOOR BACK BAR COOLER**

### EBB – Series Model : EBB59G

DIMENSIONAL DATA





Dimensions	inches	(mm)

DIMENSI	ONAL DATA			
Net capacity	/ cu. ft.	20.09 (568.9 cu l)		
	Length Overall in.	57 3/4" (1466)		
Exterior (mm)	Depth Overall in.†	27" (685)		
	Height Overall in.	37 1/4" (946)		
Crated Weight		322 lbs (146.1 kg)		
# of Doors		2		
# of Shelves	3	4		
Capacity 20	oz. (Cans / Bottles)	640 / 408		
Shelf Size L (mm)	ength x Depth in.	22 7/8" x 20 7/8" (580 x 530) 20 7/8" x 20 7/8" (530 x 530)		
ELECTRIC	CAL DATA			
Voltage (V-H	lz-Ph)	115-60-1		
Full load am	iperes	4.50		
Feed wires	with Ground	3		
Cord Length	ıft.	9		
REFRIGE	RATION DATA			
Refrigerant		R-134A		
Compressor	H.P.	1/4+ HP		
BTU/HR <sup>a</sup> (K	cal/h)	2075 (523)		
	Equipped with one N	EMA 5-15P plug.		

#### Specifications subject to change without notice.

1: Depth does not include protruding door handles.
a: Based on evaporating temperature of 23°F(-5°C) & Condensing temperature of 131°F(55°C).





Front View

