

Gas Range

(4, 6, & 10 Burner models)

Standard Features

- Stainless steel exterior including front, back sides, kick plate, back guard and over shelf
- Heavy duty 12" X 12" removable, cast iron top grates
- Drip Tray provided under burners to catch grease drippings
- 25,000 BTU top burners & 27,000 BTU oven burners
- Oven Temperature range between 175°F to 550°F
- Standing pilot for open top burners
- Oven pilot with 100% safety shut off
- Enamel interior oven for easy cleaning
- Multiple position oven rack guides
- One (1) chrome oven rack per oven standard
- Available in Natural and Propane
- 3/4" NPT rear gas connection and regulator provided

MODELS:

ATO-4B/ATO-6B/ATO-10B

ATO-4B



ATO-6B



ATO-10B



1 YR WARRANTY ON ALL PARTS AND LABOR (US ONLY)



Conforms to ANSI
STD Z83.11b-2009 (2011)
Certified for CUL
STD 1.BB-2009 (2011)
Conforms to NSF/ANSI STD.4



SPECIFICATIONS

Model	Gas type	Ignition	Burner name	Per BTU B.T.U./h	Number of Burners	Total BTU B.T.U./h	Oven size(inch)	Valve types	Net weight (lbs)	Gross weight (lbs)
ATO-4B	NG	Manually	Hot plates	25,000	4	124,000	20×26×14	Pilot light	326.1	427.5
			Oven	24,000	1	124,000				
	LP	Manually	Hot plates	23,000	4	116,000				
			Oven	24,000	1	116,000				
ATO-6B	NG	Manually	Hot plates	25,000	6	177,000	26 ¹ / ₂ ×26×14	Pilot light	440	567.9
			Oven	27,000	1	177,000				
	LP	Manually	Hot plates	23,000	6	165,000				
			Oven	27,000	1	165,000				
ATO-10B	NG	Manually	Hot plates	25,000	10	304,000	26 ¹ / ₂ ×26×14	Pilot light	732	897.3
			Oven	27,000	2	304,000				
	LP	Manually	Hot plates	23,000	10	284,000				
			Oven	27,000	2	284,000				

PLAN VIEW

