

XLERATOReco[®] HAND DRYER



500 WATTS. 10 SECONDS. NO HEAT.

NEW ENHANCED STANDARD FEATURES



Adjustable Speed and
Sound Control



Multi-Voltage Options:
110-120V Or 208-277V



Externally Visible
Service LED

10
SECONDS*
dry time

95%
COST SAVINGS
versus paper towels

80%
LESS ENERGY
than conventional dryers



XLERATOR^{eco}® HAND DRYER



MODELS: **XL - BW W GR C SB SI SP** - ECO OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



XL-BW-ECO

White Thermoset Resin (BMC)



XL-W-ECO

White Epoxy Painted



XL-GR-ECO

Graphite Textured Painted



XL-SP-ECO**

Custom Special Paint



XL-SI-ECO***

Custom Special Image



XL-C-ECO

Chrome Plated



XL-SB-ECO

Brushed Stainless Steel

DIMENSIONS

Width 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

WEIGHT

XL-BW-ECO: 15 lbs. (6.8 kgs.) **XL-SB-ECO:** 16 lbs. (7.26 kgs.)

XL-W-ECO, XL-GR-ECO, XL-C-ECO, XL-SI-ECO, XL-SP-ECO: 17 lbs. (7.71 kgs.)

ELECTRICAL

VOLTS	AMPS	WATTS	HERTZ	
110-120V	4.3-4.5A	460-530W	50/60 Hz	UL US
208-277V	2-2.2A	425-500W	50/60 Hz	UL US
230V	2.2A	500W	50 Hz	CE

NOTE: Drawing 4.5 Amps or less allows for the installation of multiple XLERATOReco units on one circuit, significantly reducing installation costs and creating a return on investment of less than one year.



RoHS



UL Environment published the first global Product Category Rules (PCR) for Hand Dryers and Excel Dryer is proud to have been selected to chair the project. The PCR created evaluation methods through industry consensus that compare products' environmental impact and performance. Third party testing results then enable specifiers and buyers to make a true apples-to-apples comparison of products and more informed decisions.



DRY TIME: 10 SECONDS*

ENERGY PER USE: 1.7 Wh*

FEATURES & BENEFITS

- ✓ 80% Less Energy Than Conventional Hand Dryers
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ Made In USA Certified®
- ✓ 5-Year Limited Warranty
- ✓ Building Green Approved and Helps Qualify for several LEED® credits
- ✓ A Hygienic Hand Drying Solution

OPTIONS

- ✓ **HEPA Filtration System:** Filters 99.97% of bacteria at 0.3 microns from the air stream.
- ✓ **1.1 Noise Reduction Nozzle:** Lowers decibel level 9 dB by reducing air deflection noise but increases dry time by approximately 3 seconds.

ONLINE INFORMATION

- ▶ Product Videos
- 💰 Cost Savings & Carbon Footprint Calculator
- 📊 Life Cycle Assessment Study
- 📄 Specification Tools
- 📄 AIA/GBCI CEU Courses
- 📄 Case Studies

ACTIVATION

Automatic Sensor Operated

MOUNTING

Surface Mounted


SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm) **Women** 43" (109 cm) **Accessible** 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

- ✓ Anti-Microbial Wall Guards
- ✓ XChanger Paper Towel Dispenser Retrofit Kit
- ✓ ADA-Compliant Recess Kit



Part # 40502

Width 16 3/8" (416 mm) **Height** 26" (660 mm)
Depth 3 3/8" (86 mm) **Weight** 11 lbs. (4.99 kgs.)

* Dry time and energy use testing performed by SGS International on standard XLERATOReco Hand Dryer with 0.8" nozzle to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.

** Special Paint powder-coated covers are available in many colors and textures.

*** Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

FEB
2017

16ECS0003