NE-21521

2100 Watt* Commercial Microwave Oven

Technical Specifications

Power source: 60Hz, Single phase

Receptacle required: NEMA 6-20R



Frequency: 2,450MHz

Required power: 208/230 V Single Phase

Output*: 2100 Watts

Outer dimensions: 16 %"w x 20"d x 13 %"h

Cavity dimensions: 13"w x 12"d x 6%"h

Net weight: 68 lbs.

Shipping weight: 73 lbs.

Warranty: 1 Year Parts, Labor and Travel/Shipping



To specify a Panasonic Commercial Microwave Oven:

The NE-21521 Commercial Microwave Oven meets or exceeds all safety performance and sanitation standards set for commercial food service microwave ovens by: UL, HHS, FCC and NSF.


Plus, oven shall have output power 2100 Watts*, Independently controlled top and bottom energy feed, Grab & Go door handle, Automatic Voltage Selector, patented Safety Door Seal System, 90 programmable memory pads, 5-stage cooking, 15 power levels, LCD digital display w/countdown, energy efficient LED cavity lighting, programmable lock, self-diagnostics, oven cycle counter, stackable, video training and Chef/Test Kitchen technical support.

* I.E.C. 705-88 Test Procedure. Specifications subject to change without notice.

Receptacle Required

NEMA Reference: Receptacle: 6-20R

Plug: 6-20P



2 Pole 3 Wire


ADA Compliance


§4.28.2 ((CFR) – 28CFR Part 36) "For Alarms".


§4.27 "For controls and operating mechanisms".













Panasonic Appliance & Commercial Group

Division of PNA Executive Offices:

One Panasonic Way, Panazip 4A-1, Secaucus, NJ 07094 Toll Free: 1-888-350-9590

www.panasonic.com/cmo