For Commercial Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative
, ippiovai	'
	SKU

Natural Gas Appliance Regulator

RV61LNG-52 (1/2 PSIG Gas System)


1" NPT Female X 1" NPT Female

RV61LNG-62 (1/2 PSIG Gas System)

1-1/4" NPT Female X 1-1/4" NPT Female

RV81LNG-72 (1/2 PSIG Gas System)

1-1/2" NPT Female X 1-1/2" NPT Female








RV61LNG-52_62, RV81LNG-72 (1/2 PSIG Gas System)


Technical Data

ITEM	CAPACITY	MAX INLET PRESSURE	TEMPERATURE LIMITS	SPRINT RANGE	SPRING Set Point	DESIGN CERTIFICATIONS
	(BTU/HR)	PSI (mbar)	Degrees Fahrenheit	" wc	" wc	CSA (C and US)
RV61LNG-52	900,000	1/2 (34)	-40 - 205	4.0 - 8.0	6	ANSI Z21.18/CSA 6.3
RV61LNG-62	900,000	1/2 (34)	-40 - 205	4.0 - 8.0	6	ANSI Z21.18/CSA 6.3
RV81LNG-72	2,500,000	1/2 (34)	-40 - 205	3.0 - 8.0	6	-









RV61LNG-52 (1/2 PSIG Gas System)

RV61LNG-62 (1/2 PSIG Gas System)

RV81LNG-72 (1/2 PSIG Gas System)

Maxitrol Regulator distributed by Dormont. Models RV61 and RV81 Series Straight-Thru-Flow Design Non-Lockup Type.

Dormont product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Dormont Technical Service. Dormont reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Dormont products previously or subsequently sold. Refer to the owner's manual for warranty information.



USA: Tel: (800) 367-6668 • Fax: (724) 733-4808 • Dormont.com **Canada:** Tel: (905) 332-4090 • Fax: (905) 332-7068 • Dormont.ca

Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • Dormont.com