

GLASS LID DISPLAY FREEZER

ULTRA

CABINET CONSTRUCTION

Sturdy design features white powder-coated steel exterior and interior.

Foamed-in-place CFC- and HCFC-free polyurethane insulation enhances the structural integrity of the cabinet and promotes energy efficiency.

Glass lid provides constant product visibility to reduce energy loss from repeatedly opening the unit.

REFRIGERATION SYSTEM

Environmentally-safe R290 refrigerant. Rear-mounted condensing unit positioned for easy maintenance,

MODEL FEATURES

2" diameter casters provide mobility for easy cleaning and service.

Drain plug located on backside of unit.

SPECIAL FEATURES

- Flat glass lid for product visibility
- Foamed-in-place polyurethane insulation
- Manual temperature controls hold at -13- 0°F
- Environmentally-friendly R290 refrigerant
- White powder-coated steel exterior & Interior
- With LED light

- Flat glass lid w/ curved front cabinet
- Interior: White pre-coated galvanized steel liner
- Integrated cabinet ABS frame
- Two (2) tempered & low emissivity sliding glass lids
- ≤ 15°F (Suitable for ice cream)
- Ventilated maintenance free condenser
- Mechanical temperature control
- Illuminated canopy
- Includes: 4 swivel casters, lock & key, wire basket(s)
- One year parts & labor warranty



Model Number	Capacity (Cu. Ft.)	Basket(s)	Dimensions (L x D x H)	Net Weight (LBS.)	Refrigerant	Rated Supply
GF-6L	5.5	1	26-1/4" x 28-1/4" x 34-2/5"	101.2	R290	115V/60HZ
GF-10L	9.5	2	40" x 28-1/4" x 34-2/5"	127.6	R290	115V/60HZ
GF-13L	13.1	3	49-3/4" x 28-1/4" x 34-2/5"	154.0	R290	115V/60HZ
GF-17L	16.6	4	60-1/4" x 28-1/4" x 34-1/2"	171.6	R290	115V/60HZ



Specifications subject to change without notice

